

CONVENTIONAL SERIES



TECHNICAL SPECIFICATIONS:

ACTIVATION: AUTOMATIC ON/OFF

MOTOR TYPE: BRUSH

DESIGNED WITH 221°F (105°C) THERMOSTAT

HEATER ASSEMBLY: DESIGNED WITH 149°F (65°C) THERMOSTAT

DRIP PROOF: 1PX1


AIR SPEED: 36.9 MPH

RPM: 5500


DECIBEL LEVEL: 73 +/-3 dB

WEIGHT: 15.4 LBS


1 YEAR WARRANTY



FRONT VIEW



SIDE VIEW



BACK MOUNTING VIEW



MODEL NO.	COVER MATERIAL	FINISH	MOUNTING OPTIONS	VOLTS	WATTS	AMPS
HD901 WH	STEEL	WHITE	SURFACE	110/120	2400	20
HD902 WH	STEEL	WHITE	SURFACE	220/240	2400	10

MODEL NO.	COVER MATERIAL	FINISH	MOUNTING OPTIONS	VOLTS	WATTS	AMPS
HD901 SS	STAINLESS STEEL	BRUSHED	SURFACE	110/120	2400	20
HD902 SS	STAINLESS STEEL	BRUSHED	SURFACE	220/240	2400	10



MODEL NO.	COVER MATERIAL	FINISH	MOUNTING OPTIONS	VOLTS	WATTS	AMPS
HD901 XS	STAINLESS STEEL	BRITE	SURFACE	110/120	2400	20
HD902 XS	STAINLESS STEEL	BRITE	SURFACE	220/240	2400	10

MOUNTING HEIGHTS:

SURFACE:

MEN	43"
WOMEN	41"
CHILDREN AGES 3-10	33"
CHILDREN AGES 11-18	39"
DISABLED	35"

RECESSED:

MEN	41"
WOMEN	39"
CHILDREN AGES 3-10	31"
CHILDREN AGES 11-18	37"
DISABLED	33"

AVERAGE TRAFFIC RESTROOMS- 1 HAND DRYER PER 2 BASINS
HIGH TRAFFIC RESTROOMS- 1 HAND DRYER PER BASIN

HAND DRYERS SHOULD BE MOUNTED BETWEEN WASH AREA AND EXIT DOOR. IF MULTIPLE UNITS ARE IN PLACE, THERE SHOULD BE A MINIMUM OF 2 FEET BETWEEN UNITS.