



# XLERATOR® HAND DRYER



MODELS: **XL - BW** **W** **GR** **C** **SB** **SI** **SP** **-H** (HEPA Filter)    OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-VOLTAGE** (See Chart)



**XL-BW**

White Thermoset Resin (BMC)



**DRY TIME: 8 SECONDS<sup>1</sup>**

**ENERGY PER USE: 3.7 Wh**



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

## FEATURES & BENEFITS

- ✓ **HEPA Filtration System:** Removes 99.999% of viruses<sup>2</sup> and 99.97% of potentially present bacteria<sup>3</sup> at 0.3 microns from the airstream.
- ✓ 50% Longer Life
- ✓ Industry Leading 7-Year Limited Warranty
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Helps Qualify For The Most LEED® Credits
- ✓ Made In USA Certified®
- ✓ A Hygienic Hand Drying Solution
- ✓ Washable Pre-Filter
- ✓ Adjustable Sensor Range

## OPTIONS

- ✓ **1.1" Noise Reduction Nozzle:** Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds.



**XL-W**

White Epoxy Painted



**XL-GR**

Graphite Textured Painted



**XL-SP<sup>4</sup>**

Custom Special Paint



**XL-SI<sup>5</sup>**

Custom Special Image



**XL-C**

Chrome Plated



**XL-SB**

Brushed Stainless Steel

## PERFORMANCE

**ADJUSTABLE SOUND LEVEL:** 65-75 dB    **ADJUSTABLE VELOCITY:** 13,000-20,000 LFM

**ADJUSTABLE HEAT RANGE:** 72°F-135°F    **ADJUSTABLE FLOW RATE:** 42-63 CFM

## DIMENSIONS

**Width** 11 3/4" (298 mm)    **Height** 12 11/16" (322 mm)    **Depth** 6 11/16" (170 mm)

## ELECTRICAL

VOLTS	AMPS	WATTS	AMPS (NO HEAT)	WATTS (NO HEAT)	HERTZ	LISTING
110-120V	11.3-12.2A	1,213-1,450W	4.3-4.5A	442-513W	50/60 Hz	cULus
208-240V	5.6-6.2A	1,135-1,450W	2.0-2.2A	416-495W	50/60 Hz	cULus
208-277V	5.6-6.2A	1,135-1,450W	2.0-2.2A	416-495W	50/60 Hz	UL
230V	6.1A	1,400W	2.1A	500W	50-60 Hz	CE

## CERTIFICATIONS



## WEIGHT

**XL-BW:** 15 lbs. (6.8 kgs.)    **XL-SB:** 16 lbs. (7.26 kgs.)    **XL-W, GR, C, SI, SP:** 17 lbs. (7.71 kgs.)

## ACTIVATION

Automatic Sensor Operated

## MOUNTING

Surface Mounted

## SUGGESTED MOUNTING HEIGHTS

**Men** 45" (114 cm)    **Women** 43" (109 cm)    **Accessible** 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

## ACCESSORIES

- ✓ Antimicrobial Wall Guards (#89B, #89W, #89S)
- ✓ XChanger® Paper Towel Dispenser Retrofit Kit (#40575, #40550)
- ✓ ADA-Compliant Recess Kit (#40502)

#40502



<sup>1</sup>Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers. <sup>2</sup>Based on testing performed by LMS Technologies, 2020. <sup>3</sup>LMS Technologies, 2014. <sup>4</sup>Special Paint powder-coated covers are available in many colors and textures. <sup>5</sup>Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



# TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

HandDryerSupply.com | 804-859-2498 | sales@handdryersupply.com

APR 2022

22EDS1087